

**Product Name // Horizontal Power Entry Module Mini  
 Bezel 48.5mm C14 Cold Condition Inlet (PX0575) 2.8mm Tab  
 Termination 1.5mm Panel A0330 Filter (3A PS01/A L/C v3)  
 Single Contact Solder Tab Illuminated Switch Marked I/O  
 Green**

[View Product Page](#)


Panel Thickness 1.0, 1.5, 2.0, 3.0mm

BZM27/\*\*\*\*\*/\*\*\* } A = 63.5 With Filter.  
 BZM28/\*\*\*\*\*/\*\*\* } A = 29.1 Without Filter.

B = 54.9 With D.P. Switch. 45.9 With S.P. Switch.  
 C = 57.5 With D.P. Switch. 48.5 With S.P. Switch.

## // Product Description:

- ⊕ Horizontal Power Entry Module Mini Bezel 57.5mm/48.5mm
- ⊕ C14 Cold Condition Inlet (PX0575)
- ⊕ Choice of Termination depending on part code:
- ⊕ Part codes prefixed BZM27: 6.3mm Tab
- ⊕ Part codes prefixed BZM42: 4.8mm Tab
- ⊕ Part codes prefixed BZM28: 2.8mm Tab
- ⊕ Choice of mains filter depending on part code:
- ⊕ Part codes containing /Z0000 are unfiltered
- ⊕ Choice of mains filter options (part codes containing codes starting /A)
- ⊕ Choice of other options as specified by individual part code, including switches with varying Terminations, indicators

## // General Information:

|                              |  |
|------------------------------|--|
| Product Display Title:       | Horizontal Power Entry Module Mini Bezel 57.5mm/48.5mm |
| Product Family:              | IEC Connectors   |
| Product Series:              | Power Entry Modules                                    |
| Current Max:                 | 3A   |
| Filter Type:                 | 3A PS01/A L/C v3                                       |
| Function:                    | C14 Inlets   |
| iec Connector Components:    | None   |
| iec Connector Mates With:    | PX0575   |
| iec Filter Options:          | A0330  |
| iec Horizontal Module Width: | 48.5mm   |
| iec Neon Colour:             | Green  |
| Inlet Type:                  | C14 Cold Condition Inlet                               |
| Max Panel Thickness:         | 1.5mm  |
| Min Panel Thickness:         | 1.5mm  |
| Switch Type:                 | Single Contact Solder Tab Marked I/O Illuminated       |
| Voltage Max:                 | 250V   |

### // Product PDF Links

[Power Entry Modules product data](#)

### // Product 3D CAD Model Links

[BZM28/A0330/A6/B3D CAD Model](#)