

**Product Name // Horizontal Power Entry Module Mini**

**Bezel 57.5mm C14 Cold Condition Inlet (PX0575) 2.8mm Tab**

**Termination 3mm Panel A1020 Filter (10A PS01/A L/C v2)**

**Double Contact 4.8mm Tab Illuminated Switch Marked I/O**

**Green**

 [View Product Page](#)



Panel Thickness 1.0, 1.5, 2.0, 3.0mm

BZM27/\*\*\*\*\*/\*\*\* } A = 63.5 With Filter.  
 BZM28/\*\*\*\*\*/\*\*\* } A = 29.1 Without Filter.

B = 54.9 With D.P. Switch. 45.9 With S.P. Switch.  
 C = 57.5 With D.P. Switch. 48.5 With S.P. Switch.

### // Product Description:

- ⊕ Horizontal Power Entry Module Mini Bezel 57.5mm/48.5mm
- ⊕ C14 Cold Condition Inlet (PX0575)
- ⊕ Choice of Termination depending on part code:
- ⊕ Part codes prefixed BZM27: 6.3mm Tab
- ⊕ Part codes prefixed BZM42: 4.8mm Tab
- ⊕ Part codes prefixed BZM28: 2.8mm Tab
- ⊕ Choice of mains filter depending on part code:
- ⊕ Part codes containing /Z0000 are unfiltered
- ⊕ Choice of mains filter options (part codes containing codes starting /A)
- ⊕ Choice of other options as specified by individual part code, including switches with varying Terminations, indicators

### // General Information:

|                              |  |
|------------------------------|--|
| Product Display Title:       | Horizontal Power Entry Module Mini Bezel 57.5mm/48.5mm |
| Product Family:              | IEC Connectors   |
| Product Series:              | Power Entry Modules                                    |
| Current Max:                 | 10A  |
| Filter Type:                 | 10A PS01/A L/C v2                                      |
| Function:                    | C14 Inlets   |
| iec Connector Components:    | None   |
| iec Connector Mates With:    | PX0575   |
| iec Filter Options:          | A1020  |
| iec Horizontal Module Width: | 57.5mm   |
| iec Neon Colour:             | Green  |
| Inlet Type:                  | C14 Cold Condition Inlet                               |
| Max Panel Thickness:         | 3mm  |
| Min Panel Thickness:         | 3mm  |
| Switch Type:                 | Double Contact 4.8mm Tab Marked I/O Illuminated        |
| Voltage Max:                 | 250V   |

#### // Product PDF Links

 [Power Entry Modules product data](#)

#### // Product 3D CAD Model Links

 [BZM28/A1020/A7/D3D CAD Model](#)