


**Product Name // Flex Cable Connector 3 Contact Plug  
 9mm-11mm Cable (White Gland)**
 [View Product Page](#)

**// Product Description:**

- ⊞ Flex Cable Connectors for hazardous areas
- ⊞ Water and dustproof to IP68 when mated with compatible connector
- ⊞ Positive fast-acting locking ring - can be turned with a gloved hand
- ⊞ Plug or Socket
- ⊞ 2, 3, 4, 5, 7, 10 Contact with leading Earth on 3, 4, 5, 7 Contact versions, trailing Neutral on 5 Contact version
- ⊞ Screw Terminals
- ⊞ Choice of cable acceptance 7mm-22mm diameter depending on part code (see data for details):
- ⊞ EXP-09 part codes 7mm-15mm diameter
- ⊞ EXP-A9 part codes (large cable version with strain relief clamp) 14mm-22mm diameter
- ⊞ Packs of Cable Glands for differing cable diameters available separately (EXP-0980, EXP-A980)
- ⊞ EXP-0990 heavy duty Sealing Cap available separately to maintain IP rating of unmated connectors
- ⊞ Mate with EXP-09 or EXP-A9 Series Flex and Panel Mounting Connectors, as appropriate

**// General Information:**

Product Display Title:	Flex Cable Connectors for hazardous areas
Product Family:	Circular Power Connectors
Product Series:	EXPlora
Approvals:	UL
Body Material:	Polyester (PET)
Body Material Type:	Plastic Body
Contact Type:	Plug Contact
Coupling Type:	Screw
Current Max:	18A
Diameter Over Coupling Ring Mm:	58mm
Flamability Rating:	UL94V-0
Function:	Flex Cable Connector
Ip Rating:	IP68
Max Cable Entry Size:	11mm
Min Cable Entry Size:	9mm
Max Contact Accomodation Awg:	14AWG
Min Contact Accomodation Awg:	10AWG
Max Contact Accomodation Mm2:	4mm <sup>2</sup>
Min Contact Accomodation Mm2:	2.5mm <sup>2</sup>
Max Operating Temperature:	+55°C
Min Operating Temperature:	-20°C
Number Of Contacts:	3 Contacts
Voltage Max:	600V

**// Product PDF Links**
 [EXPlora Series power connectors...](#)
**// Product 3D CAD Model Links**
 [EXP-0911/03/P/23D CAD Model](#)