


EXP-0911/04/S/3 Datasheet

Product Name // Flex Cable Connector EXP-0911 Series 4
Contact Socket 11mm-13mm Cable (Black Gland)

 [View Product Page](#)



// Product Description:	
- Flex Cable Connectors for hazardous areas - Water and dustproof to IP68 when mated with compatible connector - Positive fast-acting locking ring - can be turned with a gloved hand - Plug or Socket 2, 3, 4, 5, 7, 10 Contact with leading Earth on 3, 4, 5, 7 Contact versions, trailing Neutral on 5 Contact version - Screw Terminals	- Choice of cable acceptance 7mm-22mm diameter depending on part code (see data for details): - EXP-09 part codes 7mm-15mm diameter - EXP-A9 part codes (large cable version with strain relief clamp) 14mm-22mm diameter - Packs of Cable Glands for differing cable diameters available separately (EXP-0980, EXP-A980) - EXP-0990 heavy duty Sealing Cap available separately to maintain IP rating of unmated connectors - Mate with EXP-09 or EXP-A9 Series Flex and Panel Mounting Connectors, as appropriate

// General Information:	
Product Display Title:	Flex Cable Connectors for hazardous areas
Product Family:	Circular Power Connectors
Product Series:	EXPlora
Approvals:	UL
Body Material:	Polyester (PET)
Body Material Type:	Plastic Body
Contact Type:	Socket Contact
Coupling Type:	Screw
Current Max:	18A
Diameter Over Coupling Ring Mm:	58mm
Flamability Rating:	UL94V-0
Function:	Flex Cable Connector
Ip Rating:	IP68
Max Cable Entry Size:	13mm
Min Cable Entry Size:	11mm
Max Contact Accomodation Awg:	14AWG
Min Contact Accomodation Awg:	10AWG
Max Contact Accomodation Mm2:	4mm2
Min Contact Accomodation Mm2:	2.5mm2
Max Operating Temperature:	+55°C
Min Operating Temperature:	-20°C
Number Of Contacts:	4 Contacts
Voltage Max:	600V

// Product PDF Links

 [EXPlora Series power connectors...](#)

// Product 3D CAD Model Links

 [EXP-0911/04/S/33D CAD Model](#)