
## EXP-0911/10/P/3 Datasheet



## Product Name // Flex Cable Connector EXP-0911 Series 10 Contact Plug 11mm-13mm Cable (Black Gland)

View Product Page





## // Product Description:

- 0 Flex Cable Connectors for hazardous areas
- 0 Water and dustproof to IP68 when mated with compatible connector
- 0 Positive fast-acting locking ring - can be turned with a gloved
- 0 Plug or Socket
- 0 2, 3, 4, 5, 7, 10 Contact with leading Earth on 3, 4, 5, 7 Contact versions, trailing Neutral on 5 Contact version
- 0 Screw Terminals

- Choice of cable acceptance 7mm-22mm diameter depending on part code (see data for details):
- 0 EXP-09 part codes 7mm-15mm diameter
- 0 EXP-A9 part codes (large cable version with strain relief clamp) 14mm-22mm diameter
- Packs of Cable Glands for differing cable diameters available separately (EXP-0980, EXP-A980)
- 0 EXP-0990 heavy duty Sealing Cap available separately to maintain IP rating of unmated connectors
- 0 Mate with EXP-09 or EXP-A9 Series Flex and Panel Mounting Connectors, as appropriate

## // General Information:

**Product Display Title:** 

**Product Family:** 

**Product Series:** 

Approvals:

**Body Material: Body Material Type:** 

Contact Type:

Coupling Type:

**Current Max:** 

Diameter Over Coupling Ring Mm:

Flamability Rating:

Function:

Ip Rating:

Max Cable Entry Size: Min Cable Entry Size:

Max Contact Accomodation Awg:

Min Contact Accomodation Awg:

Max Contact Accomodation Mm2:

Min Contact Accomodation Mm2:

Max Operating Temperature:

Min Operating Temperature:

**Number Of Contacts:** Voltage Max:

Flex Cable Connectors for hazardous areas

Circular Power Connectors

**EXPlora** 

UL

Polyester (PET)

Plastic Body

Plug Contact Screw

58mm

UL94V-0

Flex Cable Connector

IP68 13mm

11mm

18AWG

14AWG

2.5mm2

0.75mm2 +55°C

-20°C 10 Contacts

250V

// Product PDF Links

EXPlora Series power connectors..

// Product 3D CAD Model Links



EXP-0911/10/P/33D CAD Model