
## EXP-0931/02/P Datasheet



## Product Name // Panel Mount Connector EXP-0931 Series 2 Contact Plug







## // Product Description:

- O Panel Mount Connectors for hazardous areas
- 0 Water and dustproof to IP68 when mated with compatible connector
- 0 Positive fast-acting locking ring - can be turned with a gloved hand
- O Plug or Socket
- 2, 3, 4, 5, 7, 10 Contact with leading Earth on 3, 4, 5, 7 Contact versions, trailing Neutral on 5 Contact version
- Ô Single hole fitting, anti-rotation key
- O Panel thickness 3mm-7mm
- 0 Supplied with high grade sealing gasket
- EXP-0992 heavy duty Sealing Cap available separately to maintain IP68 rating of unmated connectors
- $\bigcirc$ Mate with EXP-0911 and EXP-A911 Series Flex Connectors

## **General Information:**

**Product Display Title:** 

**Product Family: Product Series:** 

Approvals:

**Body Material:** 

**Body Material Type:** 

Contact Type:

Coupling Type:

**Current Max:** 

Diameter Over Coupling Ring Mm:

Flamability Rating:

Function:

Ip Rating:

Voltage Max:

Max Contact Accomodation Awa: Min Contact Accomodation Awg: Max Contact Accomodation Mm2: Min Contact Accomodation Mm2: Max Operating Temperature: Min Operating Temperature: **Number Of Contacts:** 

Panel Mount Connectors for hazardous areas

Circular Power Connectors

EXPlora

UL

Polyester (PET)

Plastic Body

Plug Contact

Screw 18A

58mm

UL94V-0

Front Panel Mount Connector

IP68 14AWG

10AWG

4mm2

2.5mm2

+55°C

-20°C 2 Contacts

600V

// Product 3D CAD Model Links



EXP-0931/02/P3D CAD Model