
EXP-0931/03/P Datasheet



Product Name // Panel Mount Connector EXP-0931 Series

3 Contact Plug

View Product Page



// Product Description:

- O Panel Mount Connectors for hazardous areas
- O Water and dustproof to IP68 when mated with compatible connector
- O Positive fast-acting locking ring can be turned with a gloved hand
- O Plug or Socket
- 2, 3, 4, 5, 7, 10 Contact with leading Earth on 3, 4, 5, 7 Contact versions, trailing Neutral on 5 Contact version
- O Single hole fitting, anti-rotation key
- O Panel thickness 3mm-7mm
- O Supplied with high grade sealing gasket
- O EXP-0992 heavy duty Sealing Cap available separately to maintain IP68 rating of unmated connectors
- O Mate with EXP-0911 and EXP-A911 Series Flex Connectors

// General Information:

Product Display Title: **Product Family: Product Series:** Approvals: Body Material: **Body Material Type:** Contact Type: Coupling Type: Current Max: Diameter Over Coupling Ring Mm: Flamability Rating: Function: Ip Rating: Max Contact Accomodation Awa: Min Contact Accomodation Awg: Max Contact Accomodation Mm2: Min Contact Accomodation Mm2: Max Operating Temperature: Min Operating Temperature: Number Of Contacts: Voltage Max:

Panel Mount Connectors for hazardous areas **Circular Power Connectors** EXPlora UL Polyester (PET) Plastic Body **Plug Contact** Screw 18A 58mm UL94V-0 Front Panel Mount Connector IP68 14AWG 10AWG 4mm2 2.5mm2 +55°C -20°C 3 Contacts 600V

// Product PDF Links

EXPlora Series power connectors..

// Product 3D CAD Model Links

EXP-0931/03/P3D CAD Model