# FX0380/BK Datasheet

## Product Name // Fuseholder Protection Category PC1 In-Line Black Screw Termination 5mm x 20mm Fuse

View Product Page



Image not found or type unknown

## // Product Description:

- Protection Category PC1 In-Line Fuseholders
- Screw Termination
- Part codes prefixed FX0385, FX0285, FX0185 are IP66 Sealed
- Choice of fuse size depending on part code:
- Part codes prefixed FX0380, FX0385 - 5mm x 20mm fuse
- Part codes prefixed FX0280, FX0285 - 6.3mm x 25mm fuse
- Part codes prefixed FX0180, FX0185 - 6.3mm x 32mm fuse
- Choice of colour depending on part code: Black (part codes suffixed /BK) or Clear (no suffix)
- Part codes prefixed FX0380, FX0280, FX0180 have 4.8mm diameter cable entry
- Part codes prefixed FX0385, FX0285, FX0185 have three stage stepped grommet accomodating cable diameters: 2mm - 2.64mm, 1.5mm - 1.9mm, 1mm - 1.4mm

## // General Information:

| | |
|---|---|
| **Product Display Title:** | Protection Category PC1 In-Line Fuseholders |
| **Product Family:** | Fuseholders |
| **Product Series:** | In-Line PC1 and In-Line Sealed to IP66, PC1 |
| **Change Notes:** | MK-009078-SL- |
| **Approvals:** | UL |
| **Body Material:** | Nylon 66 |
| **Current Max:** | 10A |
| **Flamability Rating:** | UL94V-0 |
| **Function:** | Pc1 Fuseholder |
| **Fuseholder Colour:** | Black |
| **Fuseholder Protection Category:** | PC1 |
| **Fuse Size:** | 5mm x 20mm |
| **Max Operating Temperature:** | +90°C |
| **Min Operating Temperature:** | -20¬?C |
| **Voltage Max:** | 50V |

### // Product PDF Links

Fuseholders product data

### // Product 3D CAD Model Links

FX0380/BK3D CAD Model

### // Product Certificate Links

UL E60600 Certificate - Black...