


PF0016/10/28/WH Datasheet

Product Name // IEC Connector Snap Fit To Panel Fused Inlet 2 Pin PF0016 Series 1mm Panel White 2.8mm Solder Tag Termination EN60 320-1 Standard Sheet C18 Class II

[View Product Page](#)



// Product Description:

- Snap Fit Panel Mount Fused IEC Inlets
- EN60 320-1 Standard Sheet C18 Class II
- Cold Condition
- Two Pin Class II (no Earth pin)
- Single 5mm x 20mm fuse
- Choice of panel thickness depending on part code: /10 - 1mm, /15 - 1.5mm, /20 - 2mm, /30 - 3mm
- Choice of Termination depending on part code: /28 - 2.8mm Solder Tag, /48 - 4.8mm Tab, /63 - 6.3mm Tab
- Choice of colour depending on part code: /WH - White, /GY - Grey, no suffix - Black (some approvals apply to specific colours only - see data for details)
- Insulation Boot for rear of connector available separately (part code 11987)
- Mate with PX0587, PX0587/SE, PX0588

// General Information:

| | |
|----------------------------|--|
| Product Display Title: | Snap Fit Panel Mount Fused IEC Inlets |
| Product Family: | IEC Connectors |
| Product Series: | IEC60320 Main Inlets and Outlets |
| Approvals: | CSA, UL, RCM |
| Body Material: | Nylon 66 |
| Current Max: | 10A |
| Flamability Rating: | UL94V-0 |
| Function: | Panel Mount Fused Connector |
| iec Connector Colour: | White |
| iec Connector Mates With: | PX0587,PX0587/SE,PX0588 |
| iec En60620 Type: | EN60 320-1 Standard Sheet C18 Class II |
| Max Operating Temperature: | +70°C |
| Min Operating Temperature: | -40°C |
| Max Panel Thickness: | 1mm |
| Min Panel Thickness: | 1mm |
| Number Of Contacts: | 2 Contacts |
| Voltage Max: | 250V |

// Product PDF Links

[IEC Connectors product data](#)

// Product 3D CAD Model Links

[PF0016/10/28/WH3D CAD Model](#)