


PF0016/20/63/WH Datasheet

Product Name // IEC Connector Snap Fit To Panel Fused
Inlet 2 Pin PF0016 Series 2mm Panel White 6.3mm Tab
Termination EN60 320-1 Standard Sheet C18 Class II

 [View Product Page](#)





List No.	DM A
PF0016/10/28	27.6
PF0016/10/48	27.6
PF0016/10/63	28.6

// Product Description:

- Snap Fit Panel Mount Fused IEC Inlets
 - EN60 320-1 Standard Sheet C18 Class II
 - Cold Condition
 - Two Pin Class II (no Earth pin)
 - Single 5mm x 20mm fuse
- Choice of panel thickness depending on part code: /10 - 1mm, /15 - 1.5mm, /20 - 2mm, /30 - 3mm
 - Choice of Termination depending on part code: /28 - 2.8mm Solder Tag, /48 - 4.8mm Tab, /63 - 6.3mm Tab
 - Choice of colour depending on part code: /WH - White, /GY - Grey, no suffix - Black (some approvals apply to specific colours only - see data for details)
 - Insulation Boot for rear of connector available separately (part code 11987)
 - Mate with PX0587, PX0587/SE, PX0588

// General Information:

Product Display Title:	Snap Fit Panel Mount Fused IEC Inlets
Product Family:	IEC Connectors
Product Series:	IEC60320 Main Inlets and Outlets
Approvals:	CSA, UL, RCM
Body Material:	Nylon 66
Current Max:	10A
Flamability Rating:	UL94V-0
Function:	Panel Mount Fused Connector
Iec Connector Colour:	White
Iec Connector Mates With:	PX0587,PX0587/SE,PX0588
Iec En60620 Type:	EN60 320-1 Standard Sheet C18 Class II
Max Operating Temperature:	+70°C
Min Operating Temperature:	-40°C
Max Panel Thickness:	2mm
Min Panel Thickness:	2mm
Number Of Contacts:	2 Contacts
Voltage Max:	250V

// Product PDF Links



// Product 3D CAD Model Links

