## PPCEGG1K04CLL Datasheet



View Product Page

bulgin

## 

## // Product Description:

- O 4 Contacts Fixed Socket 1Y Series Push Pull Connector
- O M16x1.0mm Thread
- O Nut Installation torque 7.0Nm
- O Available in Straight Plug version
- O ROHS compliance
- O IP66 rated

- O Temp:-50 C to +200 C
- O Solder Terminals
- O Durability >4500 cycles
- Operating humidity up to 95%
- O Salt Spray Corrosion Test >144h
- O High packing density for space savings on panel mounts

## // General Information:


**Product Display Title: Product Family: Product Series:** Contact Pin Material: **Coupling Nut Retention Force:** Current Max: Diameter Over Coupling Ring Mm: Durability: Fixing Nut Material: Function: Insulator: Ip Rating: Max Contact Accomodation Awg: Max Contact Accomodation Mm2: Max Operating Temperature: Min Operating Temperature: Max Panel Thickness: Number Of Contacts: **Operating Humidity:** Panel Cut Out: Pin Pin Terminal Voltage: Pin Shell Terminal Voltage: **Push Pull Connector Series: Rohs Compliant:** Salt Spray Corrosion Test: Shielding Efficiency Min: Shielding Efficiency Max: Shock Resistance: **Terminal Diameter:** Thread Size: Vibration Resistance Min: Vibration Resistance Max:


1Y Series Fixed Socket Push Pull Connector **Circular Automation Connectors** Push Pull Connectors Y Series Phosphor bronze gold plated 3u" 7Nm 10A 19.9mm >4500 cycles Nickel Plated brass Fixed Socket Push Pull Connector PPS IP66 22AWG 0.34mm2 +200°C -50°C 9.5mm 4 Contacts 0.95 16.10mmx14.60mm 1350V 1450V 1Y Series Yes 48h 95dB 80dB 100g 0.9mm M16x1.0mm 10Hz 2000Hz



// Product 3D CAD Model Links

PPCEGG1K04CLL3D CAD Model





Bulgin Datasheets 1