# PPCEGG1K08CLL Datasheet




# Product Name // 8 Contacts Fixed Socket 1Y Series Push **Pull Connector**

View Product Page

## \* Representative product image only





#### // Product Description:

- 0 8 Contacts Fixed Socket 1Y Series Push Pull Connector
- 0 M16x1.0mm Thread
- 0 Nut Installation torque 7.0Nm
- 0 Available in Straight Plug version
- 0 ROHS compliance
- 0 IP66 rated

- Temp:-50 C to +200 C
- 0 Solder Terminals
- 0 Durability >4500 cycles
- 0 Operating humidity up to 95%
- 0 Salt Spray Corrosion Test >144h
- 0 High packing density for space savings on panel mounts

### // General Information:

**Product Display Title:** 

**Product Family:** 

**Product Series:** Contact Pin Material:

**Coupling Nut Retention Force:** 

**Current Max:** 

Diameter Over Coupling Ring Mm:

**Durability:** 

Fixing Nut Material:

Function:

Insulator:

Ip Rating:

Panel Cut Out:

Max Contact Accomodation Awg: Max Contact Accomodation Mm2: Max Operating Temperature: Min Operating Temperature: Max Panel Thickness: **Number Of Contacts:** Operating Humidity:

Pin Pin Terminal Voltage: Pin Shell Terminal Voltage: **Push Pull Connector Series:** 

**Shock Resistance: Terminal Diameter:** Thread Size:

**Rohs Compliant:** Salt Spray Corrosion Test: Shielding Efficiency Min: Shielding Efficiency Max:

Vibration Resistance Min: Vibration Resistance Max: 1Y Series Fixed Socket Push Pull Connector

Circular Automation Connectors Push Pull Connectors Y Series Phosphor bronze gold plated 3u"

7Nm 5A

19.9mm >4500 cycles Nickel Plated brass

Fixed Socket Push Pull Connector

**PPS** IP66 22AWG 0.34mm2 +200°C -50°C 9.5mm 8 Contacts 0.95

950V

16.10mmx14.60mm

1150V 1Y Series Yes 48h 95dB 80dB 100g 0.7mm M16x1.0mm 10Hz 2000Hz

// Product PDF Links



// Product 3D CAD Model Links

