PPCFGG1B02CLAD Datasheet



Product Name // 2 Contacts Straight Plug 1X Series Push

Pull Connector

🚯 View Product Page

Contraction of the second seco

// Product Description:

- O 2 Contacts Straight Plug 1X Series Push Pull Connector
- O Available in Fixed Socket version
- O ROHS compliance
- O IP50 rated
- O Temp:-50 C to +200 C

- O Solder Terminals
- O Durability >4500 cycles
- Operating humidity up to 95%
- O Salt Spray Corrosion Test >144h
- O High packing density for space savings on panel mounts

// General Information:

Product Display Title: **Product Family:** Product Series: Contact Pin Material: **Current Max:** Diameter Over Coupling Ring Mm: Durability: Function: Insulator: Ip Rating: Locking Sleeve Material: Max Cable Entry Size: Min Cable Entry Size: Max Contact Accomodation Awg: Max Contact Accomodation Mm2: Max Operating Temperature: Min Operating Temperature: Number Of Contacts: **Operating Humidity:** Pin Pin Terminal Voltage: Pin Shell Terminal Voltage: Push Pull Connector Series: **Rohs Compliant:** Salt Spray Corrosion Test: Shielding Efficiency Min: Shielding Efficiency Max: Shock Resistance: **Terminal Diameter:** Vibration Resistance Min: Vibration Resistance Max:

1X Series Straight Plug Push Pull Connector **Circular Automation Connectors** Push Pull Connectors X Series Brass gold plated 3u" 15A 11.9mm >4500 cycles Straight Plug Push Pull Connector PPS IP50 Brass plated 5.0mm 4.3mm 20AWG 0.50mm2 +200°C -50°C 2 Contacts 0.95 1500V 1300V 1X Series Yes 48h 75dB 40dB 100g 1.3mm 10Hz 2000Hz

// Product PDF Links

Push-Pull Connector X Series...

// Product 3D CAD Model Links

PPCFGG1B02CLAD3D CAD Model