


PPCFGG2B19CLAD Datasheet

Product Name // 19 Contacts Straight Plug 2X Series Push Pull Connector

[View Product Page](#)



// Product Description:

- ⦿ 19 Contacts Straight Plug 2X Series Push Pull Connector
- ⦿ Solder Terminals
- ⦿ Available in Fixed Socket version
- ⦿ Durability >4500 cycles
- ⦿ ROHS compliance
- ⦿ Operating humidity up to 95%
- ⦿ IP50 rated
- ⦿ Salt Spray Corrosion Test >144h
- ⦿ Temp:-50 C to +200 C
- ⦿ High packing density for space savings on panel mounts

// General Information:

Product Display Title:	2X Series Straight Plug Push Pull Connector
Product Family:	Circular Automation Connectors
Product Series:	Push Pull Connectors X Series
Contact Pin Material:	Brass gold plated 3u"
Current Max:	5A
Diameter Over Coupling Ring Mm:	15mm
Durability:	>4500 cycles
Function:	Straight Plug Push Pull Connector
Insulator:	PPS
Ip Rating:	IP50
Locking Sleeve Material:	Brass plated
Max Cable Entry Size:	8.0mm
Min Cable Entry Size:	7.3mm
Max Contact Accomodation Awg:	22AWG
Max Contact Accomodation Mm2:	0.34mm2
Max Operating Temperature:	+200°C
Min Operating Temperature:	-50°C
Number Of Contacts:	19 Contacts
Operating Humidity:	0.95
Pin Pin Terminal Voltage:	950V
Pin Shell Terminal Voltage:	1250V
Push Pull Connector Series:	2X Series
Rohs Compliant:	Yes
Salt Spray Corrosion Test:	48h
Shielding Efficiency Min:	75dB
Shielding Efficiency Max:	40dB
Shock Resistance:	100g
Terminal Diameter:	0.7mm
Vibration Resistance Min:	10Hz
Vibration Resistance Max:	2000Hz

// Product PDF Links

[Push-Pull Connector X Series...](#)

// Product 3D CAD Model Links

[PPCFGG2B19CLAD3D CAD Model](#)