PPCFGG2K03CLAD Datasheet




Product Name // 3 Contacts Straight Plug 2Y Series Push









// Product Description:

- 0 3 Contacts Straight Plug 2Y Series Push Pull Connector
- 0 Available in Fixed Socket version
- 0 ROHS compliance
- 0 IP66 rated
- 0 Temp:-50 C to +200 C

- Solder Terminals
- 0 Durability >4500 cycles
- 0 Operating humidity up to 95%
- 0 Salt Spray Corrosion Test >144h
- High packing density for space savings on panel mounts 0

// General Information:

Product Display Title:

Product Family:

Product Series: Is Vitalis:

Contact Pin Material:

Current Max:

Diameter Over Coupling Ring Mm:

Durability: Function:

Insulator: Ip Rating:

Locking Sleeve Material: Max Cable Entry Size:

Min Cable Entry Size: Max Contact Accomodation Awg: Max Contact Accomodation Mm2: Max Operating Temperature:

Min Operating Temperature: **Number Of Contacts: Operating Humidity:** Pin Pin Terminal Voltage: Pin Shell Terminal Voltage: **Push Pull Connector Series:**

Rohs Compliant: Salt Spray Corrosion Test: Shielding Efficiency Min: Shielding Efficiency Max: Shock Resistance: **Terminal Diameter:** Vibration Resistance Min:

Vibration Resistance Max:

2Y Series Straight Plug Push Pull Connector

Circular Automation Connectors Push Pull Connectors Y Series

Brass gold plated 3u"

17A

>4500 cycles

Straight Plug Push Pull Connector

PPS IP66

Brass plated

5.0mm

4.6mm 16AWG

1.5mm2

+200°C -50°C

3 Contacts

0.95 2400V

1850V 2Y Series

Yes

48h

95dB

80dB

100g 1.6mm

10Hz 2000Hz

// Product PDF Links

Push-Pull Connector Y Series...

// Product 3D CAD Model Links

PPCFGG2K03CLAD3D CAD Model

Click Here To Contact Us