
PPCFGG3B10CLAD Datasheet



Product Name // 10 Contacts Straight Plug 3X Series Push **Pull Connector**

View Product Page





// Product Description:

- 0 10 Contacts Straight Plug 3X Series Push Pull Connector
- 0 Available in Fixed Socket version
- 0 ROHS compliance
- 0 IP50 rated
- 0 Temp:-50 C to +200 C

- Solder Terminals
- 0 Durability >4500 cycles
- 0 Operating humidity up to 95%
- 0 Salt Spray Corrosion Test >144h
- 0 High packing density for space savings on panel mounts

// General Information:

Product Display Title:

Product Family:

Product Series: Contact Pin Material:

Current Max:

Diameter Over Coupling Ring Mm:

Durability:

Function:

Insulator: Ip Rating:

Locking Sleeve Material:

Max Cable Entry Size:

Min Cable Entry Size: Max Contact Accomodation Awg:

Max Contact Accomodation Mm2:

Max Operating Temperature: Min Operating Temperature:

Number Of Contacts:

Operating Humidity:

Pin Pin Terminal Voltage:

Pin Shell Terminal Voltage: **Push Pull Connector Series:**

Rohs Compliant:

Salt Spray Corrosion Test: Shielding Efficiency Min:

Shielding Efficiency Max:

Shock Resistance:

Terminal Diameter: Vibration Resistance Min:

Vibration Resistance Max:

3X Series Straight Plug Push Pull Connector

Circular Automation Connectors

Push Pull Connectors X Series

Brass gold plated 3u"

>4500 cycles

Straight Plug Push Pull Connector

PPS

IP50

Brass plated 7.0mm

6.3mm

20AWG

0.50mm2 +200°C

-50°C

10 Contacts

0.95 1250V

900V

3X Series Yes

48h

75dB

40dB

100g

1.3mm

10Hz 2000Hz

// Product PDF Links

Push-Pull Connector X Series...

// Product 3D CAD Model Links

PPCFGG3B10CLAD3D CAD Model