## PPCFGG3K24CLAD Datasheet




## Product Name // 24 Contacts Straight Plug 3Y Series Push **Pull Connector**









## // Product Description:

- 0 24 Contacts Straight Plug 3Y Series Push Pull Connector
- 0 Available in Fixed Socket version
- 0 ROHS compliance
- 0 IP66 rated
- 0 Temp:-50 C to +200 C

- Solder Terminals
- 0 Durability >4500 cycles
- 0 Operating humidity up to 95%
- 0 Salt Spray Corrosion Test >144h
- High packing density for space savings on panel mounts 0

## // General Information:

**Product Display Title:** 

**Product Family:** 

**Product Series:** 

Is Vitalis:

Contact Pin Material:

**Current Max:** 

Diameter Over Coupling Ring Mm:

Durability: Function:

Insulator: Ip Rating:

Locking Sleeve Material: Max Cable Entry Size:

Min Cable Entry Size: Max Contact Accomodation Awg: Max Contact Accomodation Mm2: Max Operating Temperature: Min Operating Temperature:

**Number Of Contacts: Operating Humidity:** Pin Pin Terminal Voltage: Pin Shell Terminal Voltage: **Push Pull Connector Series:** 

**Rohs Compliant:** Salt Spray Corrosion Test: Shielding Efficiency Min: Shielding Efficiency Max: **Shock Resistance: Terminal Diameter:** Vibration Resistance Min:

Vibration Resistance Max:

3Y Series Straight Plug Push Pull Connector

Circular Automation Connectors Push Pull Connectors Y Series

Brass gold plated 3u"

4A

19mm

>4500 cycles

Straight Plug Push Pull Connector PPS

IP66

Brass plated 11.0mm

10.6mm

22AWG 0.34mm2

+200°C

-50°C

24 Contacts 0.95

950V

800V 3Y Series

Yes

48h

95dB

80dB 100g

0.7mm

10Hz 2000Hz

// Product PDF Links

Push-Pull Connector Y Series...

// Product 3D CAD Model Links

PPCFGG3K24CLAD3D CAD Model