PX0100S02GY Datasheet

Product Name // 2 Contacts Male Standard Rectangular Grey Connector

View Product Page





// Product Description:

- 2 Contacts Male Standard Rectangular Grey Connector
- Enhanced Seal Protection (ESR), Protective End Cap (PEC), Terminating Resistor (TER), Shrink Boot Adapter (SBA), Welded Flange (WFL) and Y-Type Connector (YTY) Available
- Water and dustproof to IP68 when mated with compatible connector
- Mate with PX0101 Series, as appropriate
- Wedgelocks provided
- Crimp Terminals
- Mechanical Cycles = 100 (min)
- Operating Temperature = -25°C to +120°C

// General Information:

Product Display Title:	2 Contacts Male Standard Rectangular Grey Connector
Product Family:	Rectangular Connectors
Product Series:	Standard Rectangular Connectors
Body Colour:	Grey
Body Material:	Polycarbonate/Polybutylene Terephthalate (PC/PBT)
Body Material Type:	Plastic Body
Contact Type:	Socket Contact
Coupling Type:	Snap-in
Current Max:	13A
Ip Rating:	IP68
Max Operating Temperature:	+120°C
Min Operating Temperature:	-40°C
Number Of Contacts:	2 Contacts
Voltage Max:	250V

// Product PDF Links

Rectangular Connector Datasheet

// Product 3D CAD Model Links

PX0100S02GY3D CAD Model