
PX0101P04BK Datasheet



Product Name // 4 Contacts Female Standard Rectangular Black Connector





// Product Description:

- 4 Contacts Female Standard Rectangular Black Connector
- Enhanced Seal Protection (ESR), Protective End Cap (PEC), Terminating Resistor (TER), Shrink Boot Adapter (SBA), Welded Flange (WFL) and Y-Type Connector (YTY) Available
- Water and dustproof to IP68 when mated with compatible connector
- Mate with PX0 100 Series, as appropriate

- Wedgelocks provided
- O Crimp Terminals
- O Mechanical Cycles = 100 (min)
- Operating Temperature = -25°C to +120°C

// General Information:

Product Display Title:

Product Family:

Product Series: Body Colour:

Body Material:

Body Material Type:

Contact Type:

Coupling Type:

Current Max: Ip Rating:

Max Operating Temperature:

Min Operating Temperature:

Number Of Contacts: Voltage Max: 4 Contacts Female Standard Rectangular Black Connector

Rectangular Connectors

Standard Rectangular Connectors

Black

Polycarbonate/Polybutylene Terephthalate (PC/PBT)

Plastic Body Plug Contact

Snap-in

13A

IP68 +120°C

-40°C

4 Contacts

250V

// Product PDF Links

Rectangular Connector Datasheet

// Product 3D CAD Model Links

PX0101P04BK3D CAD Model