


**Product Name // Overmould Flex Cable Connector PX0400**  
**Series Pre-Wired 3M Cable 12 Contact Plug**
 [View Product Page](#)

**// Product Description:**

- ⬢ Overmoulded Flex Connector pre-wired cable assemblies
- ⬢ Water and dustproof to IP68 when mated with compatible connector
- ⬢ Pin or Socket
- ⬢ 2, 3, 4, 6, 8, 10 or 12 Contact
- ⬢ Cable acceptance 2.5mm-9mm
- ⬢ Choice of cable length depending on part code
- ⬢ PX0481 Sealing Cap available separately to maintain IP rating of unmated connectors
- ⬢ Mate with PX0401, PX0411 Inline Connectors and PX0412, PX0413 Panel Mount Connectors

**// General Information:**

Product Display Title:	Overmoulded Flex Connector pre-wired cable assemblies
Product Family:	Circular Power Connectors
Product Series:	400 Series Buccaneer
Approvals:	CSA, UL, VDE
Body Material:	Polyurethane (PU)
Contact Type:	Plug Contact
Coupling Type:	Screw
Current Max:	1A
Diameter Over Coupling Ring Mm:	19.1mm
Flamability Rating:	UL94V-HB
Function:	Flex Connector Single Ended Cable
Ip Rating:	IP68, IP69K
Max Operating Temperature:	+85°C
Min Operating Temperature:	-20°C
Number Of Contacts:	12 Contacts
Voltage Max:	50V

**// Product PDF Links**
 [400 Series power connectors...](#)
**// Product 3D CAD Model Links**
 [PX0400/003/12P3D CAD Model](#)