PX0410/02S/5560 Datasheet




Product Name // Flex Cable Connector PX0410 Series 2 Contact Socket 5.5mm-6.0mm Cable









// Product Description:

- 0 Flex Cable Connector
- 0 Water and dustproof to IP68 when mated with compatible connector
- 0 Pin or Socket
- 0 2, 3, 4, 6, 8, 10 or 12 Contact
- 0 Crimp or Solder Contacts available (supplied separately; use 8A for 2/3 Contact, 5A for 4/6/8 Contact, 1A for 10/12 Contact)
- Contact insertion and crimp tools available (supplied separately)
- 0 Choice of cable acceptance 3mm-7mm depending on part code; supplied with Cable Gland and Collet colour coded by size
- 0 PX0481 Sealing Cap available separately to maintain IP rating of unmated connectors
- Mate with Inline or Panel Mount Connectors PX0401, PX0411, PX0412, PX0413

// General Information:

Product Display Title: Product Family: Product Series: Is Vitalis:

Approvals: **Body Material: Body Material Type:** Contact Type: Coupling Type:

Diameter Over Coupling Ring Mm:

Flamability Rating: Function:

Current Max:

Ip Rating: Max Cable Entry Size: Min Cable Entry Size: Max Contact Accomodation Awg:

Min Contact Accomodation Awg: Max Contact Accomodation Mm2: Min Contact Accomodation Mm2: Max Operating Temperature: Min Operating Temperature: **Number Of Contacts:** Voltage Max:

Flex Cable Connector Circular Power Connectors

400 Series Buccaneer

No

Polyamide (PA) Plastic Body Socket Contact Screw

8A 19.1mm UL94V-0

Flex Cable Connector

IP68 6.0mm 5.5mm 24AWG 20AWG 0.5mm2 0.25mm2 +80°C -40°C 2 Contacts 250V

// Product PDF Links // Product 3D CAD Model Links



400 Series power connectors...



400 Series power connectors wiring...

PX0410/02S/55603D CAD Model

