
PX0410/12P/6570 Datasheet



Product Name // Flex Cable Connector PX0410 Series 12 Contact Plug 6.5mm-7.0mm Cable

View Product Page



// Product Description:

- 0 Flex Cable Connector
- 0 Water and dustproof to IP68 when mated with compatible connector
- 0 Pin or Socket
- 0 2, 3, 4, 6, 8, 10 or 12 Contact
- 0 Crimp or Solder Contacts available (supplied separately; use 8A for 2/3 Contact, 5A for 4/6/8 Contact, 1A for 10/12 Contact)
- Contact insertion and crimp tools available (supplied separately)
- 0 Choice of cable acceptance 3mm-7mm depending on part code; supplied with Cable Gland and Collet colour coded by size
- 0 PX0481 Sealing Cap available separately to maintain IP rating of
- Mate with Inline or Panel Mount Connectors PX0401, PX0411, PX0412, PX0413

// General Information:

Product Display Title: Product Family: Product Series: Approvals:

Body Material: Body Material Type: Contact Type:

Coupling Type: **Current Max:**

Diameter Over Coupling Ring Mm:

Flamability Rating:

Function: Ip Rating:

Max Cable Entry Size: Min Cable Entry Size:

Max Contact Accomodation Awg: Min Contact Accomodation Awg: Max Contact Accomodation Mm2: Min Contact Accomodation Mm2: **Max Operating Temperature:** Min Operating Temperature:

Number Of Contacts: Voltage Max:

Flex Cable Connector Circular Power Connectors 400 Series Buccaneer

Polyamide (PA) Plastic Body Plug Contact Screw 1A 19.1mm UL94V-0

Flex Cable Connector

IP68 7.0mm 6.5mm 28AWG 24AWG 0.25mm2 0.08mm2 +80°C -40°C 12 Contacts 50V

// Product PDF Links 400 Series power connectors wiring... // Product 3D CAD Model Links