


# PX0411/12S/4045 Datasheet

**Product Name** // Inline Cable Connector PX0411 Series 12  
**Contact Socket 4.0mm-4.5mm Cable**

 [View Product Page](#)



### // Product Description:

- Inline Cable Connector
  - Water and dustproof to IP68 when mated with compatible connector
  - Pin or Socket
  - 2, 3, 4, 6, 8, 10 or 12 Contact
  - Crimp or Solder Contacts available (supplied separately; use 8A for 2/3 Contact, 5A for 4/6/8 Contact, 1A for 10/12 Contact)
- Contact insertion and crimp tools available (supplied separately)
  - Choice of cable acceptance 3mm-7mm depending on part code; supplied with Cable Gland and Collet colour coded by size
  - PX0480/1 Sealing Cap available separately to maintain IP rating of unmated connectors
  - Mate with Flex Cable Connectors PX0400, PX0402, PX0410

### // General Information:

|                                 |                           |
|---------------------------------|---------------------------|
| Product Display Title:          | Inline Cable Connector    |
| Product Family:                 | Circular Power Connectors |
| Product Series:                 | 400 Series Buccaneer      |
| Approvals:                      | UL                        |
| Body Material:                  | Polyamide (PA)            |
| Body Material Type:             | Plastic Body              |
| Contact Type:                   | Socket Contact            |
| Coupling Type:                  | Screw                     |
| Current Max:                    | 1A                        |
| Diameter Over Coupling Ring Mm: | 19.1mm                    |
| Flamability Rating:             | UL94V-0                   |
| Function:                       | Inline Cable Connector    |
| Ip Rating:                      | IP68                      |
| Max Cable Entry Size:           | 4.5mm                     |
| Min Cable Entry Size:           | 4.0mm                     |
| Max Contact Accomodation Awg:   | 28AWG                     |
| Min Contact Accomodation Awg:   | 24AWG                     |
| Max Contact Accomodation Mm2:   | 0.25mm2                   |
| Min Contact Accomodation Mm2:   | 0.08mm2                   |
| Max Operating Temperature:      | +80°C                     |
| Min Operating Temperature:      | -40°C                     |
| Number Of Contacts:             | 12 Contacts               |
| Voltage Max:                    | 50V                       |

#### // Product PDF Links

-  400 Series power connectors...
-  400 Series power connectors wiring...

#### // Product 3D CAD Model Links

-  PX0411/12S/40453D CAD Model



Have a question or project enquiry  
you'd like to talk to us about?



[Click Here To Contact Us](#)