
PX0477/C/C/1M00 Datasheet

Product Name // 400 Series USB-C Cable Assembly, Flex USB-C To USB-C, 1m

View Product Page





// Product Description:

- Overmoulded C-Type USB 3.2 Gen 2x2 Cable
- Standard USB Type C plug to Sealed C-Type USB plug
- Flex USB-C end sealed to IP68 when mated with compatible connector
- 1m cable length
- 20Gbps transfer speed, 240W charging
- PX0485 Sealing Cap available separately to maintain IP rating of unmated connectors
- Mates with PX0472 and PX0473 panel mount connectors

// General Information:

Product Display Title:	IP-sealed ‘C’ type to Standard ‘C’ type USB, 1m of Cable
Product Family:	Circular Data Connectors
Product Series:	400 Data Connectors
Body Material:	PVC/Nylon
Body Material Type:	Plastic Body
Cable Length:	1m
Contact Type:	Plug Contact
Coupling Type:	Screw
Flamability Rating:	UL94V-0
Ip Rating:	IP67, IP68
Max Operating Temperature:	+70°C
Min Operating Temperature:	-35°C
Number Of Contacts:	24 Contacts

// Product PDF Links

400 Series C Type USB Buccaneer...

// Product 3D CAD Model Links

PX0477/C/C/1M003D CAD Model