



⬢ Flange Mount IEC Inlets ⬢ EN60 320-1 Standard Sheet C14 Class I ⬢ Cold Condition ⬢ Choice of Termination depending on part code: /28 - 2.8mm Solder Tag, /48 - 4.8mm Tab, /63 - 6.3mm Tab, /TERM - Screw Terminal, /PC - PCB Spills ⬢ PCB Mount version also available with additional 4.8mm Tab Earth connection at top of connector (part codes containing /PC/7)	⬢ Choice of colour depending on part code: /WH - White, /GY - Grey, no suffix - Black (some approvals apply to specific colours only - see data for details) ⬢ PCB Mount version without additional Earth Tab (part codes containing /PC) available with rear cover (part codes suffixed /12132), for all other versions Insulation Boot for rear of connector available separately (part code 11328) ⬢ Retaining Clip KT0006 available separately to prevent accidental removal of mating connector (for use with PX0587 Female Connector only) ⬢ Mate with PX0587, PX0587/SE, PX0588 ⬢ Also available as Vertical Flange Mount (PX0579 Series)
---	--

Product Display Title:	Flange Mount IEC Inlets
Product Family:	IEC Connectors
Product Series:	IEC60320 Main Inlets and Outlets
Approvals:	CSA, UL
Body Material:	Nylon 66
Current Max:	15A
Flamability Rating:	UL94V-0
Function:	Flange Mount Connector
Iec Connector Colour:	Grey
Iec Connector Mates With:	PX0587,PX0587/SE,PX0588
Iec En60620 Type:	EN60 320-1 Standard Sheet C14 Class I
Max Operating Temperature:	+70°C
Min Operating Temperature:	-40°C
Number Of Contacts:	3 Contacts
Voltage Max:	250V

 IEC Connectors product data **PX0580/28/GY3D CAD Model** CE Certificate - PX0580