


# PX0595/15/48/GY Datasheet

**Product Name // IEC Connector Snap Fit To Panel Inlet**  
**PX0595 Series 1.5mm Panel Grey 4.8mm Tab Termination**  
**EN60 320-1 Standard Sheet C15 and C16 Class I**

[View Product Page](#)



## // Product Description:

- ⊕ Snap Fit Panel Mount IEC Inlets
- ⊕ EN60 320-1 Standard Sheet C15 and C16 Class I
- ⊕ Hot Condition
- ⊕ Choice of panel thickness depending on part code: /10 - 1mm, /15 - 1.5mm, /20 - 2mm, /30 - 3mm
- ⊕ Choice of Termination depending on part code: /28 - 2.8mm Solder Tag, /48 - 4.8mm Tab, /63 - 6.3mm Tab, /TERM - Screw Terminal
- ⊕ Choice of colour depending on part code: /WH - White, /GY - Grey, no suffix - Black (some approvals apply to specific colours only - see data for details)
- ⊕ Insulation Boot for rear of connector available separately (part code 11328)
- ⊕ Mate with PX0597

## // General Information:

Product Display Title:	Snap Fit Panel Mount IEC Inlets
Product Family:	IEC Connectors
Product Series:	IEC60320 Main Inlets and Outlets
Approvals:	CSA, UL
Body Material:	Nylon 66
Current Max:	15A
Flamability Rating:	UL94V-0
Function:	Panel Mount Connector
iec Connector Colour:	Grey
iec Connector Mates With:	PX0597
iec En60620 Type:	EN60 320-1 Standard Sheet C15 and C16 Class I
Max Operating Temperature:	+70°C
Min Operating Temperature:	-40°C
Max Panel Thickness:	1.5mm
Min Panel Thickness:	1.5mm
Number Of Contacts:	3 Contacts
Voltage Max:	250V

### // Product PDF Links

[IEC Connectors product data](#)

### // Product 3D CAD Model Links

[PX0595/15/48/GY3D CAD Model](#)