


**Product Name // Pre-Wired Overmould Flex Cable  
Connector PX0700 Range 12 Contact Plug Black Insert**

[View Product Page](#)


**// Product Description:**

- ◊ Pre-Wired Overmoulded Flex Connector cable assemblies
- ◊ Water and dustproof to IP68 when mated with compatible connector
- ◊ Plug or Socket
- ◊ 2, 3, 4, 6, 7, 9, 12, 25 Contact with leading Earth contact on 3 Contact Socket versions
- ◊ Cable acceptance up to 14mm diameter with PVC or PU jackets
- ◊ PX0734 Sealing Cap available separately to maintain IP rating of unmated connectors
- ◊ Mate with PX07 Series Inline and Panel Mount Connectors

**// General Information:**

Product Display Title:	Pre-Wired Overmoulded Flex Connector cable assemblies
Product Family:	Circular Power Connectors
Product Series:	Standard Buccaneer
Approvals:	CSA, UL, VDE
Body Material:	Polyamide (PA)- Glass Filled
Contact Type:	Plug Contact
Coupling Type:	Screw
Current Max:	5A
Diameter Over Coupling Ring Mm:	38.1mm
Flamability Rating:	UL94HB
Function:	Flex Connector Single Ended Cable
Insert Colour:	Black Insert
Ip Rating:	IP68, IP69K
Max Operating Temperature:	+70°C
Min Operating Temperature:	-20°C
Number Of Contacts:	12 Contacts
Voltage Max:	50V

**// Product PDF Links**

[Standard Series power connectors...](#)

**// Product 3D CAD Model Links**

[PX0700/P/123D CAD Model](#)