


PX0700/P/03 Datasheet

Product Name // Pre-Wired Overmould Flex Cable
Connector PX0700 Series 3 Contact Plug Black Insert

 [View Product Page](#)



// Product Description:	
- Pre-Wired Overmoulded Flex Connector cable assemblies - Water and dustproof to IP68 when mated with compatible connector - Plug or Socket 2, 3, 4, 6, 7, 9, 12, 25 Contact with leading Earth contact on 3 Contact Socket versions	- Cable acceptance up to 14mm diameter with PVC or PU jackets - PX0734 Sealing Cap available separately to maintain IP rating of unmated connectors - Mate with PX07 Series Inline and Panel Mount Connectors

// General Information:	
Product Display Title:	Pre-Wired Overmoulded Flex Connector cable assemblies
Product Family:	Circular Power Connectors
Product Series:	Standard Buccaneer
Approvals:	CSA, UL, VDE
Body Material:	Polyamide (PA)- Glass Filled
Contact Type:	Plug Contact
Coupling Type:	Screw
Current Max:	10A, 12A
Diameter Over Coupling Ring Mm:	38.1mm
Flamability Rating:	UL94HB
Function:	Flex Connector Single Ended Cable
Insert Colour:	Black Insert
Ip Rating:	IP68, IP69K
Max Operating Temperature:	+70°C
Min Operating Temperature:	-20°C
Number Of Contacts:	3 Contacts
Voltage Max:	277V

// Product PDF Links

 Standard Series power connectors...