

Product Name // Rear Panel Mount Connector PX0709
Range 2 Contact Socket Screw Termination (Contacts Supplied Fitted) Blue Insert

[View Product Page](#)


// Product Description:

- ⊗ Rear Panel Mount Connectors
- ⊗ Water and dustproof to IP68 when mated with compatible connector
- ⊗ Single hole fixing
- ⊗ Plug or Socket
- ⊗ 2, 3, 4, 6, 7, 9, 12, 25 Contact with leading Earth contact on 3 Contact Socket versions
- ⊗ Screw, Crimp, Crimp/Solder Terminations available depending on part code and number of Contacts
- ⊗ Screw contacts supplied fitted, Crimp contacts supplied loose (Crimp/Solder contacts and fitting tools available separately)
- ⊗ Choice of coloured inserts to enable positive visual identification of connector:
- ⊗ Part codes suffixed with a colour code followed by 2 have that colour insert
- ⊗ Colour choices and colour codes: Blue (BL), Green (GN), Grey (GY), Light Grey (LG), Red (RD), White (WH), Yellow (YL), Black (standard colour, no suffix code)
- ⊗ PX0711 Sealing Cap available separately to maintain IP rating of unmated connectors
- ⊗ Mate with PX07 Series Flex Connectors

// General Information:

| | |
|---------------------------------|-----------------------------|
| Product Display Title: | Rear Panel Mount Connectors |
| Product Family: | Circular Power Connectors |
| Product Series: | Standard Buccaneer |
| Approvals: | CSA, UL, VDE |
| Body Material: | Polyamide (PA) |
| Body Material Type: | Plastic Body |
| Contact Type: | Socket Contact |
| Coupling Type: | Screw |
| Current Max: | 10A, 12A |
| Diameter Over Coupling Ring Mm: | 38.1mm |
| Flamability Rating: | UL94V-0 |
| Function: | Rear Panel Mount Connector |
| Insert Colour: | Blue Insert |
| Ip Rating: | IP68, IP69K |
| Max Operating Temperature: | +70°C |
| Min Operating Temperature: | -20°C |
| Number Of Contacts: | 2 Contacts |
| Voltage Max: | 277V |

// Product PDF Links

[Standard Series power connectors...](#)
[Standard Series power connectors...](#)

// Product 3D CAD Model Links

[PX0709/S/02/BL23D CAD Model](#)