
### PX0739/P/07/GY1 Datasheet



## Product Name // Flex Cable Connector PX0739 Series 6 Contact Plug Screw Termination (Contacts Supplied Fitted) 7mm-9mm Cable Grey Insert And Gland Nut







#### // Product Description:

- O Flex Cable Connectors
- Water and dustproof to IP68 when mated with compatible connector
- Plug or Socket
- Q 2, 3, 4, 6, 7, 9, 12, 25 Contact with leading Earth contact on 3 Contact Socket versions
- O Screw, Crimp, Crimp/Solder Terminations depending on part code and number of Contacts
- Screw contacts supplied fitted, Crimp contacts supplied loose (Crimp/Solder contacts and fitting tools available separately)
- Choice of cable acceptance 3.5mm-9mm diameter depending on part code (see data for details)
- Cable Glands for differing cable diameters available separately individually or in packs
- Cable Support accessory 12237 available separately to provide extra support for smaller cables (5mm-9mm diameter)
- O Choice of coloured inserts/gland nuts to enable positive visual identification of connector:
- Part codes suffixed with a colour code followed by 2 have that colour insert with black gland nut, part codes suffixed with a colour code followed by 1 have the same colour insert and gland nut
- Colour choices and colour codes: Blue (BL), Green (GN), Grey (GY), Light Grey (LG), Red (RD), White (WH), Yellow (YL), Black (standard colour, no suffix code)
- PX0734 Sealing Cap available separately to maintain IP rating of unmated connectors
- Mate with PX07 Series Inline and Panel Mount Connectors

#### // General Information:

Product Display Title:

Product Family: Product Series:

Product Series

Approvals: Body Materia

Body Material: Body Material Type:

Contact Type:

Coupling Type:

Current Max:

Diameter Over Coupling Ring Mm:

Flamability Rating: Function:

Insert Colour:

Max Cable Entry Size:

Min Cable Entry Size:

**Number Of Contacts:** 

Voltage Max:

Max Contact Accomodation Awg:
Min Contact Accomodation Awg:
Max Contact Accomodation Mm2:
Min Contact Accomodation Mm2:
Max Operating Temperature:
Min Operating Temperature:

Flex Cable Connectors

Circular Power Connectors Standard Buccaneer

UL

Polyamide (PA)- Glass Filled

Plastic Body Plug Contact

Screw 5A 38.1mm

UL94HB Flex Cable Connector

Grey Insert And Gland Nut

IP68 9mm 7mm 17AWG 16AWG

1.5mm2 1mm2 +70°C -20°C

6 Contacts

277V

# // Product PDF Links Standard Series power connectors...

// Product 3D CAD Model Links

PX0739/P/07/GY13D CAD Model