
## PX0757/S/LG2 Datasheet



## **Product Name // Bulkhead Flange Mount Connector PX0757 Series 2 Contact Socket Screw Termination** (Contacts Supplied Fitted) Light Grey Insert







## // Product Description:

- 0 Bulkhead Flange Mount Connectors
- 0 Water and dustproof to IP68 when mated with compatible connector
- 0 Screw fixing flange, supplied with sealing gasket and screw sealing grommets
- 0 Plug or Socket
- 2, 3, 4, 6, 7, 9, 12, 25 Contact with leading Earth contact on 3 Contact Socket versions
- Screw, Crimp, Crimp/Solder Terminations available, depending on part code and number of Contacts
- O Screw contacts supplied fitted, Crimp contacts supplied loose (Crimp/Solder contacts and fitting tools available separately)
- Choice of coloured inserts to enable positive visual identification of connector:
- 0 Part codes suffixed with a colour code followed by 2 have that colour insert
- 0 Colour choices and colour codes: Blue (BL), Green (GN), Grey (GY), Light Grey (LG), Red (RD), White (WH), Yellow (YL), Black (standard colour, no suffix code)
- PX0733 Sealing Cap available separately to maintain IP rating of unmated connectors
- Mate with PX07 Series Flex Connectors

## **General Information:**

**Product Display Title:** 

**Product Family: Product Series:** 

Approvals:

**Body Material:** 

Contact Type:

Coupling Type:

**Current Max:** 

Diameter Over Coupling Ring Mm:

Flamability Rating:

Function:

Insert Colour:

Ip Rating:

Max Operating Temperature: Min Operating Temperature: **Number Of Contacts:** 

Voltage Max:

Circular Power Connectors

Bulkhead Flange Mount Connectors

Standard Buccaneer

CSA, UL, VDE

Polyamide (PA)- Glass Filled

Socket Contact

Screw

10A, 12A 38.1mm

UL94HB

Bulkhead Flange Mount Connector

Light Grey Insert

IP68, IP69K

+70°C -20°C

2 Contacts

277V



Standard Series power connectors..



Standard Series power connectors.

// Product 3D CAD Model Links

PX0757/S/LG23D CAD Model