PX0796/P/WH2 Datasheet



Product Name // Front Panel Mount Connector PX0796 Series 12 Contact Plug Crimp/Solder Termination (Contacts Available Separately) White Insert

View Product Page

5.2 Max. Panel.
0.8 Min. Panel.

DIMENSION A. : OLE, PLUG, SOCKET,



// Product Description:

- Front Panel Mount Connectors
- Water and dustproof to IP68 when mated with compatible connector
- O Single hole fixing
- O Plug or Socket
- 2, 3, 4, 6, 7, 9, 12, 25 Contact with leading Earth contact on 3 Contact Socket versions
- Screw, Crimp, Crimp/Solder Terminations available depending on part code and number of Contacts
- O Screw contacts supplied fitted, Crimp contacts supplied loose (Crimp/Solder contacts and fitting tools available separately)
- Choice of coloured inserts to enable positive visual identification of connector:
- Part codes suffixed with a colour code followed by 2 have that colour insert
- Colour choices and colour codes: Blue (BL), Green (GN), Grey (GY), Light Grey (LG), Red (RD), White (WH), Yellow (YL), Black (standard colour, no suffix code)
- O PX0799 rear of panel back shell and 12855 Insulation Boot available separately
- PX0733 Sealing Cap available separately to maintain IP rating of unmated connectors
- O Mate with PX07 Series Flex Connectors

// General Information:

Product Display Title: Product Family:

Product Series: Approvals: Body Material:

Body Material Type: Contact Type:

Coupling Type: Current Max:

Diameter Over Coupling Ring Mm:

Flamability Rating: Function:

Insert Colour: Ip Rating:

Max Operating Temperature: Min Operating Temperature: Number Of Contacts: Voltage Max: Front Panel Mount Connectors
Circular Power Connectors

Standard Buccaneer

CSA, UL, VDE


Polyamide (PA)- Glass Filled

Plastic Body Plug Contact Screw 5A

38.1mm UL94HB

Front Panel Mount Connector

White Insert IP68, IP69K +70°C -20°C 12 Contacts 50V





Click Here To Contact Us