


# PX0798/S/WH2 Datasheet

**Product Name // Bulkhead Flange Mount Connector**  
**PX0798 Series 12 Contact Socket Crimp/Solder Termination**  
**(Contacts Available Separately) White Insert**

 [View Product Page](#)



// **Product Description:**

- ⬢ Bulkhead Flange Mount Connectors
  - ⬢ Water and dustproof to IP68 when mated with compatible connector
  - ⬢ Screw fixing flange, supplied with sealing gasket and screw sealing grommets
  - ⬢ Plug or Socket
  - ⬢ 2, 3, 4, 6, 7, 9, 12, 25 Contact with leading Earth contact on 3 Contact Socket versions
  - ⬢ Screw, Crimp, Crimp/Solder Terminations available, depending on part code and number of Contacts
- ⬢ Screw contacts supplied fitted, Crimp contacts supplied loose (Crimp/Solder contacts and fitting tools available separately)
  - ⬢ Choice of coloured inserts to enable positive visual identification of connector:
  - ⬢ Part codes suffixed with a colour code followed by 2 have that colour insert
  - ⬢ Colour choices and colour codes: Blue (BL), Green (GN), Grey (GY), Light Grey (LG), Red (RD), White (WH), Yellow (YL), Black (standard colour, no suffix code)
  - ⬢ PX0733 Sealing Cap available separately to maintain IP rating of unmated connectors
  - ⬢ Mate with PX07 Series Flex Connectors

// **General Information:**

|                                 |                                  |
|---------------------------------|----------------------------------|
| Product Display Title:          | Bulkhead Flange Mount Connectors |
| Product Family:                 | Circular Power Connectors        |
| Product Series:                 | Standard Buccaneer               |
| Approvals:                      | CSA, UL, VDE                     |
| Body Material:                  | Polyamide (PA)- Glass Filled     |
| Contact Type:                   | Socket Contact                   |
| Coupling Type:                  | Screw                            |
| Current Max:                    | 5A                               |
| Diameter Over Coupling Ring Mm: | 38.1mm                           |
| Flamability Rating:             | UL94HB                           |
| Function:                       | Bulkhead Flange Mount Connector  |
| Insert Colour:                  | White Insert                     |
| Ip Rating:                      | IP68, IP69K                      |
| Max Operating Temperature:      | +70°C                            |
| Min Operating Temperature:      | -20°C                            |
| Number Of Contacts:             | 12 Contacts                      |
| Voltage Max:                    | 50V                              |

// **Product PDF Links**

-  [Standard Series power connectors...](#)
-  [Standard Series power connectors...](#)