


Product Name // **Inline Cable Connector PX0921 Range 5****Contact Plug 13mm-15mm Cable (Yellow Gland)**
[View Product Page](#)


// Product Description:

- ◊ Inline Cable Connectors
- ◊ Water and dustproof to IP68 when mated with compatible connector
- ◊ Positive fast-acting locking ring - can be turned with a gloved hand
- ◊ Plug or Socket
- ◊ 2, 3, 4, 5, 7, 10 Contact with leading Earth on 3, 4, 5, 7 Contact versions, trailing Neutral on 5 Contact version
- ◊ Screw Terminals
- ◊ Choice of cable acceptance 7mm-22mm diameter depending on part code (see data for details):
- ◊ PX09 part codes 7mm-15mm diameter
- ◊ PXA9 part codes (large cable version with strain relief clamp) 14mm-22mm diameter
- ◊ Packs of Cable Glands for differing cable diameters available separately (PX0980, PXA980)
- ◊ PX0970/PX0991 Sealing Caps available separately to maintain IP rating of unmated connectors
- ◊ Mate with PX0911 or PXA911 Series Flex Connectors, as appropriate

// General Information:

Product Display Title:	Inline Cable Connectors
Product Family:	Circular Power Connectors
Product Series:	900 Series Buccaneer
Approvals:	UL
Body Material:	Polyamide (PA)
Body Material Type:	Plastic Body
Contact Type:	Plug Contact
Coupling Type:	Screw
Current Max:	32A
Diameter Over Coupling Ring Mm:	58mm
Flamability Rating:	UL94V-0
Function:	Inline Cable Connector
IP Rating:	IP68
Max Cable Entry Size:	15mm
Min Cable Entry Size:	13mm
Max Contact Accommodation Awg:	13AWG
Min Contact Accommodation Awg:	10AWG
Max Contact Accommodation Mm ² :	4mm ²
Min Contact Accommodation Mm ² :	2.6mm ²
Max Operating Temperature:	+85°C
Min Operating Temperature:	-40°C
Number Of Contacts:	5 Contacts
Voltage Max:	600V

// Product PDF Links


[900 Series power connectors...](#)

[900 Series power connectors wiring...](#)

// Product 3D CAD Model Links


[PX0921/05/P3D CAD Model](#)