## PXA911/02/P/09 Datasheet



View Product Page

## Product Name // Flex Cable Connector Large Cable PXA911 Series 2 Contact Plug 18mm-20mm Cable (Black Gland)



## // Product Description:

- 0 Flex Cable Connectors
- 0 Water and dustproof to IP68 when mated with compatible connector
- 0 Positive fast-acting locking ring - can be turned with a gloved hand
- 0 Plug or Socket
- 0 2, 3, 4, 5, 7, 10 Contact with leading Earth on 3, 4, 5, 7 Contact versions, trailing Neutral on 5 Contact version
- 0 Screw Terminals


- Ó Choice of cable acceptance 7mm-22mm diameter depending on part code (see data for details):
- PX09 part codes 7mm-15mm diameter 0
- 0 PXA9 part codes (large cable version with strain relief clamp) 14mm-22mm diameter
- 0 Packs of Cable Glands for differing cable diameters available separately (PX0980, PXA980)
- 0 PX0960/PX0990 Sealing Caps available separately to maintain IP rating of unmated connectors
- 0 Mate with PX09 or PXA9 Series Flex and Panel Mount Connectors, as appropriate

## **General Information:** //

**Product Display Title: Product Family: Product Series:** Approvals: **Body Material: Body Material Type:** Contact Type: Coupling Type: **Current Max:** Diameter Over Coupling Ring Mm: Flamability Rating: Function: Ip Rating: Max Cable Entry Size: Min Cable Entry Size: Max Contact Accomodation Awg: Min Contact Accomodation Awg: Max Contact Accomodation Mm2: Min Contact Accomodation Mm2: Max Operating Temperature: Min Operating Temperature: Number Of Contacts: Voltage Max:

Flex Cable Connectors **Circular Power Connectors** 900 Series Buccaneer UL Polyamide (PA) Plastic Body Plug Contact Screw 32A 58mm UL94V-0 Flex Cable Connector IP68 20mm 18mm 13AWG 10AWG 4mm2 2.6mm2 +85°C -40°C 2 Contacts 600V





Click Here To Contact Us

**Bulgin Datasheets** 1