PXA911/04/P/07 Datasheet



View Product Page

Product Name // Flex Cable Connector Large Cable PXA911 Series 4 Contact Plug 14mm-16mm Cable (Dark Grey Gland)



// Product Description:

- Flex Cable Connectors
- O Water and dustproof to IP68 when mated with compatible connector
- O Positive fast-acting locking ring can be turned with a gloved hand
- O Plug or Socket
- 2, 3, 4, 5, 7, 10 Contact with leading Earth on 3, 4, 5, 7 Contact versions, trailing Neutral on 5 Contact version
- O Screw Terminals


- Choice of cable acceptance 7mm-22mm diameter depending on part code (see data for details):
- O PX09 part codes 7mm-15mm diameter
- PXA9 part codes (large cable version with strain relief clamp)
 14mm-22mm diameter
- Packs of Cable Glands for differing cable diameters available separately (PX0980, PXA980)
- PX0960/PX0990 Sealing Caps available separately to maintain IP rating of unmated connectors
- Mate with PX09 or PXA9 Series Flex and Panel Mount Connectors, as appropriate

// General Information:

Product Display Title: Product Family: Product Series: Approvals: **Body Material: Body Material Type:** Contact Type: Coupling Type: **Current Max:** Diameter Over Coupling Ring Mm: Flamability Rating: Function: Ip Rating: Max Cable Entry Size: Min Cable Entry Size: Max Contact Accomodation Awg: Min Contact Accomodation Awg: Max Contact Accomodation Mm2: Min Contact Accomodation Mm2: Max Operating Temperature: Min Operating Temperature: Number Of Contacts: Voltage Max:

Flex Cable Connectors **Circular Power Connectors** 900 Series Buccaneer UL Polyamide (PA) Plastic Body Plug Contact Screw 32A 58mm UL94V-0 Flex Cable Connector IP68 16mm 14mm 13AWG 10AWG 4mm2 2.6mm2 +85°C -40°C 4 Contacts 600V





Click Here To Contact Us

Bulgin Datasheets 1