


**Product Name // 2 Channel Plug Connector**
 [View Product Page](#)
**// Product Description:**

- ⊕ Non-terminated Plug Connector for a 2-Channel Multimode Cable with 4-4.5mm Diameter
- ⊕ Designed to MIL-DTL83526D
- ⊕ Compatible with any connector that follows MIL-DTL83526D
- ⊕ Compatible with OM1 & OM3
- ⊕ Dust Cap, Lanyard, and Ferrules (termini) for the Cable Included
- ⊕ Mates with Plug, Jam Nut, and Flange Mount Connectors (hermaphroditic)
- ⊕ Operating Temperature -50°C to +80°C
- ⊕ Available in 4 Channel
- ⊕ Cable Assembly Available

**// General Information:**

Product Display Title:	2 Channel Plug Connector
Product Family:	Circular Fiber Connectors
Product Series:	5000 Series Expanded Beam
Max Insertion Loss:	<2dB
Avg Insertion Loss:	<1.5dB
Body Colour:	Dark Grey
Body Material:	Polycarbonate/Polybutylene Terephthalate (PC/PBT)
Body Material Type:	Plastic Body
Contact Type:	Expanded Beam
Coupling Type:	Screw
Diameter Over Coupling Ring Mm:	30mm
Fibre Mode:	MM
Flamability Rating:	UL94V-0
Function:	EB Plug Connector
Ip Rating:	IP68
Material Finish:	Matt
Max Cable Entry Size:	4.5mm
Min Cable Entry Size:	4mm
Max Operating Temperature:	+80°C
Min Operating Temperature:	-50°C
Rohs Compliant:	Yes

**// Product PDF Links**
 [5000 Series Expanded Beam Product...](#)
**// Product 3D CAD Model Links**
 [PXEB5200MM40453D CAD Model](#)