PXEB5201C050 Datasheet

Product Name // 2 Channel Plug to Plug Connector Cable

🚯 View Product Page

bulgin

* Representative product image only

// Product Description:

Assembly

Two-terminated Plug Connectors with a 2-Channel OM3
Outdoor Tactical Cable - 50m Long Cable Assembly

- O Designed to MIL-DTL83526D
- O Compatible with any connector that follows MIL-DTL83526D
- O Dust Cap & Lanyard included for each Connector
- Mates with Plug, Jam Nut, & Flange Mount Connectors (hermaphroditic)
- Operating Temperature -50°C to +80°C
- Available in 4 Channel
- O Available in Plug to LC & Plug to SC Cable Assembly

// General Information:

Product Display Title: Product Family: **Product Series:** Max Insertion Loss: Avg Insertion Loss: Body Colour: Body Material: Body Material Type: Contact Type: Coupling Type: Diameter Over Coupling Ring Mm: Fibre Mode: Flamability Rating: Function: Ip Rating: Material Finish: Max Operating Temperature: Min Operating Temperature: **Rohs Compliant:**

2 Channel Plug to Plug Connector Cable Assembly **Circular Fiber Connectors** 5000 Series Expanded Beam <2dB <1.5dB Dark Grey Polycarbonate/Polybutylene Terephthalate (PC/PBT) Plastic Body Expanded Beam Screw 30mm OM3 UL94V-0 EB Plug to Plug Double Ended Fiber Cable IP68 Matt +80°C -50°C Yes

// Product PDF Links

5000 Series Expanded Beam Product...

// Product 3D CAD Model Links

PXEB5201C0503D CAD Model