PXEB5400MM5055 Datasheet

Product Name // 4 Channel Plug Connector

View Product Page

bulgin



// Product Description:

- Non-terminated Plug Connector for a 4-Channel Multimode Cable with 5-5.5mm Diameter
- O Designed to MIL-DTL83526D
- O Compatible with any connector that follows MIL-DTL83526D
- O Compatible with OM1 & OM3
- O Dust Cap, Lanyard, and Ferrules (termini) for the Cable Included
- Mates with Plug, Jam Nut, and Flange Mount Connectors (hermaphroditic)
- O Operating Temperature -50°C to +80°C
- O Available in 2 Channel
- O Cable Assembly Available

// General Information:

Product Display Title: Product Family: **Product Series:** Max Insertion Loss: Ava Insertion Loss: Body Colour: **Body Material:** Body Material Type: Contact Type: Coupling Type: Diameter Over Coupling Ring Mm: Fibre Mode: Flamability Rating: Function: Ip Rating: Material Finish: Max Cable Entry Size: Min Cable Entry Size: Max Operating Temperature: Min Operating Temperature: **Rohs Compliant:**

4 Channel Plug Connector **Circular Fiber Connectors** 5000 Series Expanded Beam <2dB <1.5dB Dark Grey Polycarbonate/Polybutylene Terephthalate (PC/PBT) Plastic Body Expanded Beam Screw 30mm MM UL94V-0 **EB Plug Connector** IP68 Matt 5.5mm 5mm +80°C -50°C Yes

// Product PDF Links

5000 Series Expanded Beam Product...

// Product 3D CAD Model Links

PXEB5400MM50553D CAD Model