
PXEB5401B015 Datasheet



Product Name // 4 Channel Plug to Plug Connector Cable Assembly







// Product Description:

- Two-terminated Plug Connectors with a 4-Channel OM1
 Outdoor Tactical Cable 15m Long Cable Assembly
- O Designed to MIL-DTL83526D
- O Compatible with any connector that follows MIL-DTL83526D
- O Dust Cap & Lanyard included for each Connector
- Mates with Plug, Jam Nut, & Flange Mount Connectors (hermaphroditic)
- Operating Temperature -50°C to +80°C
- Available in 2 Channel
- O Available in Plug to LC & Plug to SC Cable Assembly

// General Information:

Product Display Title: 4 Channel Plug to Plug Connector Cable Assembly

Product Family:Circular Fiber ConnectorsProduct Series:5000 Series Expanded Beam

 Max Insertion Loss:
 <2dB</td>

 Avg Insertion Loss:
 <1.5dB</td>

 Body Colour:
 Dark Grey

Body Material: Polycarbonate/Polybutylene Terephthalate (PC/PBT)

Body Material Type: Plastic Body
Contact Type: Expanded Beam
Coupling Type: Screw

Diameter Over Coupling Ring Mm: 30mm

Fibre Mode: OM1
Flamability Rating: UL94V-0

Function: EB Plug to Plug Double Ended Fiber Cable Ip Rating: IP68

Material Finish: Matt
Max Operating Temperature: +80°C
Min Operating Temperature: -50°C

// Product 3D CAD Model Links

Yes

PXEB5401B0153D CAD Model



Rohs Compliant:

