
PXEB5402C450 Datasheet



Product Name // 4 Channel Plug to LC Connector Cable Assembly





// Product Description:

- A Terminated Plug Connector with a 4-Channel OM3 Outdoor Tactical Cable that breaks out in 2 independent cables (0.5m long) with LC Terminations - 450m Long Cable Assembly
- O Designed to MIL-DTL83526D
- O Compatible with any connector that follows MIL-DTL83526D
- O Dust Cap for all Connectors & Plug Lanyard Included
- Mates with Plug, Jam Nut, & Flange Mount Connectors (hermaphroditic)
- Operating Temperature -50°C to +80°C
- O Available in 2 Channel
- O Available in Plug to Plug & Plug to SC Cable Assembly

// General Information:

Product Display Title: 4 Channel Plug to LC Connector Cable Assembly

 Product Family:
 Circular Fiber Connectors

 Product Series:
 5000 Series Expanded Beam

Max Insertion Loss: <2dB

Avg Insertion Loss: <1.5dB

Body Colour: Dark Grey

Body Material: Polycarbonate/Polybutylene Terephthalate (PC/PBT)

Body Material Type:Plastic BodyContact Type:Expanded BeamCoupling Type:Screw

Diameter Over Coupling Ring Mm:30mmFibre Mode:OM3

Flamability Rating: UL94V-0
Function: EB Plug to LC Double Ended Fiber Cable

Ip Rating:IP68Material Finish:Matt

Max Operating Temperature: +80°C
Min Operating Temperature: -50°C
Rohs Compliant: Yes

// Product PDF Links

5000 Series Expanded Beam Product.

