

# PXEB5403B010 Datasheet



## Product Name // 4 Channel Plug to SC Connector Cable **Assembly**







#### // Product Description:

- A Terminated Plug Connector with a 4-Channel OM1 Outdoor Tactical Cable that breaks out in 2 independent cables (0.5m long) with SC Terminations - 10m Long Cable Assembly
- O Designed to MIL-DTL83526D
- O Compatible with any connector that follows MIL-DTL83526D
- O Dust Cap for all Connectors & Plug Lanyard Included
- Mates with Plug, Jam Nut, & Flange Mount Connectors (hermaphroditic)
- 0 Operating Temperature -50°C to +80°C
- 0 Available in 2 Channel
- O Available in Plug to Plug & Plug to LC Cable Assembly

#### // General Information:

**Product Display Title:** 4 Channel Plug to SC Connector Cable Assembly

**Product Family:** Circular Fiber Connectors **Product Series:** 5000 Series Expanded Beam

<2dB Max Insertion Loss: Avg Insertion Loss: <1.5dB **Body Colour:** Dark Grev

**Body Material:** Polycarbonate/Polybutylene Terephthalate (PC/PBT) **Body Material Type:** Plastic Body

Contact Type: Expanded Beam Screw Coupling Type:

30mm Diameter Over Coupling Ring Mm: OM1 Fibre Mode:

Flamability Rating: UL94V-0 Function: EB Plug to SC Double Ended Fiber Cable

IP68 Ip Rating: Material Finish: Matt Max Operating Temperature: +80°C

Min Operating Temperature: -50°C **Rohs Compliant:** Yes

### // Product PDF Links





Click Here To Contact Us



1