
PXEB5413C001 Datasheet



Product Name // 4 Channel Jam Nut to SC Connector **Cable Assembly**

View Product Page





// Product Description:

- O A Terminated Jam Nut Bulkhead (JNBH) Connector with 4 (OM3) SC terminated independent cables - 1m Long Cable Assembly
- 0 Designed to MIL-DTL83526D
- 0 Compatible with any connector that follows MIL-DTL83526D
- 0 Dust Cap for all Connectors & Jam Nut Lanyard Included
- \bigcirc Mates with Plug Connectors (hermaphroditic)
- 0 Operating Temperature -50°C to +80°C
- 0 Available in 2 Channel
- \bigcirc Available in Jam Nut to LC Cable Assembly

General Information:

Product Display Title: 4 Channel Jam Nut to SC Connector Cable Assembly

Product Family: Circular Fiber Connectors 5000 Series Expanded Beam **Product Series:**

Max Insertion Loss: <2dR

Avg Insertion Loss: <1.5dB **Body Colour:** Dark Grey

Body Material: Polycarbonate/Polybutylene Terephthalate (PC/PBT)

Body Material Type: Plastic Body Contact Type: Expanded Beam Coupling Nut Retention Force: 1Nm

Screw Coupling Type: Diameter Over Coupling Ring Mm: 30mm

Fibre Mode: ОМЗ Flamability Rating: UL94V-0

EB Jam Nut to SC Double Ended Fiber Cable Function: Ip Rating: **IP68**

Material Finish: Max Operating Temperature: Min Operating Temperature: Max Panel Thickness:

Matt +80°C -50°C 4.7mm Yes

// Product PDF Links

Rohs Compliant:

5000 Series Expanded Beam Product..

// Product 3D CAD Model Links

PXEB5413C0013D CAD Model