
PXF4050 Datasheet



Product Name // No Cable, Flex fiber connector

View Product Page



// Product Description:

- 0 Flex Fiber Connector
- 0 Sealed to IP66, IP68, IP69K when mated with compatible connector
- O no cable options, or pre-terminated from 5M - 450M available
- 0 Simplex LC type fiber connector

- Choices of OS1, OM1 and OM3 cables for single or multimode
- O PXP4081 Sealing Cap available separately to maintain IP rating of unmated connectors
- 0 Mate with Inline fiber connector or panel mount connectors PXF4051, PXF4053

// General Information:

Product Display Title:

Product Family:

Product Series:

Is Vitalis: **Body Material:**

Body Material Type:

Contact Type: Coupling Type:

Diameter Over Coupling Ring Mm:

Fibre Mode:

Flamability Rating: Function:

Ip Rating:

Max Operating Temperature: Min Operating Temperature:

Flex Fiber Connector

Circular Fiber Connectors

4000 Series - Simplex LC Fiber Buccaneer

Polycarbonate/Polybutylene Terephthalate (PC/PBT)

Plastic Body

LC Fiber

30 Degree coupling

19.7mm

OS₁

UL94V-0

Flex Fiber Connector IP66, IP68, IP69K

+70°C

-20°C



