
## PXF4050BAG Datasheet



## Product Name // 200 M, Multimode, Cabled, Flex fiber connector





## **Product Description:**

- 0 Flex Fiber Connector to LC type Connector
- 0 Sealed to IP66, IP68, IP69K when mated with compatible connector
- 0 no cable options, or pre-terminated from 5M - 450M available
- 0 Simplex LC type fiber connector

- Choices of OS1, OM1 and OM3 cables for single or multimode
- O PXP4081 Sealing Cap available separately to maintain IP rating of unmated connectors
- 0 Mate with Inline fiber connector or panel mount connectors PXF4051, PXF4053

## // General Information:

**Product Display Title:** 

**Product Family: Product Series:** 

Is Vitalis:

**Body Material:** 

Contact Type:

Coupling Type:

Diameter Over Coupling Ring Mm:

Fibre Mode:

Flamability Rating:

Function:

Ip Rating:

Max Operating Temperature: Min Operating Temperature:

Flex Fiber Connector to LC type Connector

Circular Fiber Connectors

4000 Series - Simplex LC Fiber Buccaneer

Polycarbonate/Polybutylene Terephthalate (PC/PBT)

LC Fiber 30 Degree coupling

19.7mm OM1

UL94V-0

Flex to LC Connector Double Ended Fiber Cable

IP66, IP68, IP69K

+70°C

-20°C

