
## PXF4051 Datasheet



## Product Name // No Cable, Inline fiber connector





## // Product Description:

- 0 Inline Fiber Connector
- 0 Sealed to IP66, IP68, IP69K when mated with compatible connector
- O no cable options, or pre-terminated from 5M - 450M available
- 0 Simplex LC type fiber connector

- Choices of OS1, OM1 and OM3 cables for single or multimode
- 0 PXP4082 Sealing Cap available separately to maintain IP rating of unmated connectors
- O Mate with flex fiber connector PXF4050

## // General Information:

**Product Display Title:** 

**Product Family:** 

**Product Series:** 

Is Vitalis: **Body Material:** 

**Body Material Type:** 

Contact Type:

Coupling Type:

Diameter Over Coupling Ring Mm:

Fibre Mode:

Flamability Rating: Function:

Ip Rating:

Max Operating Temperature: Min Operating Temperature:

Inline Fiber Connector

Circular Fiber Connectors

4000 Series - Simplex LC Fiber Buccaneer

Polycarbonate/Polybutylene Terephthalate (PC/PBT)

Plastic Body

LC Fiber

30 Degree coupling

19.7mm

OS<sub>1</sub>

UL94V-0

Inline Fiber connector IP66, IP68, IP69K

+70°C

-20°C



