
PXF4054CAC Datasheet



Product Name // 25 M, Multimode, Cabled, Flex fiber connector





// Product Description:

- O Flex Fiber Connector to Inline Fiber Connector
- Sealed to IP66, IP68, IP69K when mated with compatible connector
- O no cable options, or pre-terminated from 5M 450M available
- O Simplex LC type fiber connector

- O Choices of OS1, OM1 and OM3 cables for single or multimode
- PXP4081 Sealing Cap available separately to maintain IP rating of unmated connectors
- Mate with Inline fiber connector or panel mount connectors PXF4051, PXF4053

// General Information:

Product Display Title:

Product Family:

Product Series:

Body Material:

Contact Type:

Coupling Type:

Diameter Over Coupling Ring Mm:

Fibre Mode:

Flamability Rating: Function:

runction

Ip Rating:

Max Operating Temperature: Min Operating Temperature:

Flex Fiber Connector to Inline Fiber Connector

Circular Fiber Connectors

4000 Series - Simplex LC Fiber Buccaneer

Polycarbonate/Polybutylene Terephthalate (PC/PBT)

LC Fiber

30 Degree coupling

19.7mm

ОМЗ

UL94V-0

Flex to LC Connector Double Ended Fiber Cable

IP66, IP68, IP69K

+70°C

-20°C



