
# **PXF6050A Datasheet**



## Product Name // No Cable, Flex fiber connector for OM3 cable





#### // Product Description:

- 0 Flex Fiber Connector
- 0 Sealed to IP66, IP68, IP69K when mated with compatible connector
- 0 no cable options, or pre-terminated from 5M - 450M available
- 0 Duplex LC type fiber connector

- Choices of OS1, OM1 and OM3 cables for single or multimode
- 0 PXP6083 Sealing Cap available separately to maintain IP rating of unmated connectors
- 0 Mate with Inline fiber connector or panel mount connectors PXF6051, PXF6052

### // General Information:

**Product Display Title:** 

**Product Family:** 

**Product Series:** 

Is Vitalis:

**Body Material: Body Material Type:** 

Contact Type:

Coupling Type:

Diameter Over Coupling Ring Mm:

Fibre Mode:

Flamability Rating: Function:

Ip Rating:

Max Operating Temperature: Min Operating Temperature:

Flex Fiber Connector

Circular Fiber Connectors

6000 Series - Duplex LC Fiber Buccaneer

Polyamide (PA)

Plastic Body

LC Fiber

30 Degree coupling

32mm OM3

UL94V-0

Flex Fiber Connector IP66, IP68, IP69K

+70°C

-25°C

#### // Product PDF Links



6000 Series Fiber connectors.

### // Product 3D CAD Model Links



PXF6050A3D CAD Model