
PXF6050CAH Datasheet



Product Name // 200 M, OS1 Single Mode, Cabled, Flex fiber connector





// Product Description:

- O Flex Fiber Connector to LC type connector
- Sealed to IP66, IP68, IP69K when mated with compatible connector
- O no cable options, or pre-terminated from 5M 450M available
- O Duplex LC type fiber connector

- O Choices of OS1, OM1 and OM3 cables for single or multimode
- PXP6083 Sealing Cap available separately to maintain IP rating of unmated connectors
- Mate with Inline fiber connector or panel mount connectors PXF6051, PXF6052

// General Information:

Product Display Title:

Product Family:

Product Series:

Body Material:

Contact Type:

Coupling Type:

Diameter Over Coupling Ring Mm:

Fibre Mode:

Flamability Rating:

Function:

Ip Rating:

Max Operating Temperature: Min Operating Temperature:

Flex Fiber Connector to LC type Connector

Circular Fiber Connectors

6000 Series - Duplex LC Fiber Buccaneer

Polyamide (PA)

LC Fiber

30 Degree coupling

32mm

OS1

UL94V-0

Flex to Double LC Connector Double Ended Fiber Cable

IP66, IP68, IP69K

+70°C

-25°C



6000 Series Fiber connectors...





PXF6050CAH3D CAD Model