


PXF6051B Datasheet

Product Name // No Cable, Inline fiber connector for OM1 cable

[View Product Page](#)



// Product Description:

- ⬡ Inline Fiber Connector
- ⬡ Sealed to IP66, IP68, IP69K when mated with compatible connector
- ⬡ no cable options, or pre-terminated from 5M - 450M available
- ⬡ Duplex LC type fiber connector
- ⬡ Choices of OS1, OM1 and OM3 cables for single or multimode
- ⬡ PXP6081 Sealing Cap available separately to maintain IP rating of unmated connectors
- ⬡ Mate with flex fiber connector PXF6050

// General Information:

Product Display Title:	Inline Fiber Connector
Product Family:	Circular Fiber Connectors
Product Series:	6000 Series - Duplex LC Fiber Buccaneer
Body Material:	Polyamide (PA)
Body Material Type:	Plastic Body
Contact Type:	LC Fiber
Coupling Type:	30 Degree coupling
Diameter Over Coupling Ring Mm:	32mm
Fibre Mode:	OM1
Flamability Rating:	UL94V-0
Function:	Inline Fiber connector
Ip Rating:	IP66, IP68, IP69K
Max Operating Temperature:	+70°C
Min Operating Temperature:	-25°C

// Product PDF Links

[6000 Series Fiber connectors...](#)

// Product 3D CAD Model Links

[PXF6051B3D CAD Model](#)